
















TECHNICAL DATA SHEET AltroSmooth Chrysalis

| | | | |
|---------------------|---|--------|----------------------|
| Product Description | Decorative PVC smooth vinyl flooring with PUR coating. | | |
| Areas of Use | Shops, schools, hospitals, and corridors/circulation areas. | | |
| Thickness |  | EN 428 | 2.0mm |
| Weight |  | EN 430 | 3.0kg/m ² |
| Roll dimensions |  | EN 426 | 2 x 20m |
| Wear Layer |  | EN429 | 2.0mm |
| Colours | 16 | | |
| Warranty | 5 years | | |

| | | | |
|-------------------------------------|---|---|--|
| Product Approval |  | EN 649 | Approved |
| Classification For Use |  | EN 685 | 34/43 |
| Light Fastness |  | EN 20105-B02 | >6 |
| Slip Resistance |  | EN13893 | DS |
| Wear Resistance |  | EN660-1 | ≤ 0.15mm Group P |
| Indentation |  | EN 433 | <0.1mm |
| Fire Performance |  | EN 13501-1 EN ISO 9239-1 EN ISO 11925-2 | Bfl s1 >8kw/cm ² Pass |
| Chemical Resistance |  | EN 423 | Good Resistance * |
| Castor Chair Abrasion |  | EN 425 | Satisfactory |
| Suitability for Under Floor Heating |  | EN 12 524 | Suitable 0.25 W/(mK) |
| Biocidal |  | Biocidal | Incorporates Biocide |

* please contact Altro Technical Services for further information