


















Technical Data Sheet - Altro Suprema II™

Colours	40		
Warranty	10 years		
Flooring Type		EN 13845/ EN 13553	Safety flooring Suelo de seguridad antideslizante Sicherheitsbodenbelag
Classification for use		EN 685	34 & 43 34 y 43 34 & 43
Slip Resistance		TRRL EN 13845 EN 13893 DIN 51130	≥ 36 ESf DS R10
Thickness		EN 428	2 mm
Flexibility		EN 435	Pass Conforme bestanden
Wear Layer		EN 429	0.8mm
Weight		EN 430	2.4 kg/m ²
Roll Dimensions		EN 426	2 m x 20 m = 40m ²
Light Fastness		EN 20105-B02	>6
Sound Insulation		ISO 140-8	5 dB
Wear Resistance		EN 13845	<10% particles lost over 50000 Cycles <10% de las partículas perdidas en 50.000 ciclos < 10% Partikel werden über 50000 Umdrehungen verloren
Indentation		EN 433	< 0.10mm
Fire Performance		EN 13501-1 EN ISO 9239-1 EN ISO 11925-2	Class Bfl-s1 >8kW/m ² Pass Clase Bfl-s1 >8kW/m ² Conforme Klasse Bfl-s1 >8kW/m ² , bestanden
Chemical Resistance		EN 423	Good Buena beständig
Castor Chair Abrasion		EN 425	Pass Conforme geeignet
Under floor heating		EN 12667	Suitable Apto geeignet
Electrical Behaviours		EN 1815	< 2kV Antistatic < 2kV Antiestáticas < 2kV antistatisch